

TriWave™ Series: The Next Wave in Seeding is Here.



TriWave™ 45



TriWave™ 60

TriWave Working directly with golf course superintendents, Turfco® designed the innovative **TriWave™ 60 Overseeder**. In 2016 the innovation continued with the introduction of the **TriWave™ 45 Overseeder**. Now you can get enhanced seeding performance with an evolutionary model that hooks up to your favorite turf vehicle.

TriWave's 1½-inch seed spacing, combined with three independent floating heads, greatly increases germination by following the contours of the terrain for consistent seed depth. Its WaveBlade technology creates clean, optimal slit widths for better seed-to-soil contact while keeping turf disruption to a minimum. The patented delivery system

places seed directly into the slit, reducing waste while further increasing germination. And, seed depth can be infinitely adjusted in the field to suit the needs of each situation.

If you want to get great germination with less disruption, demo a TriWave Overseeder. As with the many superintendents who helped in its development, you'll find the TriWave truly makes a difference on your course.

- Patent-pending floating heads follow the ground contour—you won't miss the low spots or destroy the high spots or unmarked sprinkler heads.



- Patented seed delivery system puts seed directly into

the slit, reducing waste and increasing germination.


- Patented WaveBlade technology, counter-rotating at 900RPM, creates a clean, optimal square slit while minimizing turf disruption.
- Patented depth adjustment allows for infinite, in-field adjustment to suit your specific needs. No tools required.
- Close, 1½-inch spacing increases germination with fewer passes.




Allows cross-seeding with minimal disruption.



Patent-pending seed diverter increases germination by placing seed directly into the slit.



Traditional overseeders create a v-shaped slit, causing inconsistent contact that the seed has with the soil.



The TriWave maximizes seed to soil contact at the right depth with a square slit that quickly closes.



WaveBlade technology creates optimum clean slits, increasing seed-to-soil contact.



Minimal disruption to turf.

TriWave™ 45 Overseeder



Go Green Anywhere on Your Course

Damaged turf on your #7 tee? Weak areas on your #2 and #12 greens? Want to improve the overall stand of grass on your high traffic areas? With the TriWave™ 45, greening up your course has never been easier or quicker. You can go green now—you don't have to wait for the grass to come back next season. Just hook it up to your turf vehicle and quickly seed all your trouble spots in one trip. No tools are required to quickly adjust seed rates and depths to match the conditions you need. Now's the time to take your course to the next level.

- Hooks up to your favorite turf vehicle and seeds while you turn so you can follow greens, collars and contours. No tractor or PTOs required.
- Dual 18-inch floating heads follow the contour of the ground while the patented seed delivery system works with the WaveBlade technology to optimize seed-to-soil contact with minimal turf disruption.
- Close, 1 1/2-inch spacing increases germination with fewer passes.
- Easy to switch out green blades and fairway blades.



Patented floating heads follow the contour of the ground, optimizing seed-to-soil contact for better germination.



Proven 30 percent higher germination results vs traditional methods. Better germination with less seed.



Quick-adjust depth control allows you to get the right seed depth in varying conditions.

Specifications

Model	TriWave 45 Overseeder w/ Fairway Blades (comes standard) (#85858) TriWave 45 Overseeder w/ Green Blades (optional) (#85859)
Width	66" (1.67 m)
Height	56.5" (1.43 m)
Length	80.5" (2.05 m)
Capacity	3.2 ft³ (0.09 m³) Approx. 50 lb of grass seed
Application Pattern	Seed spacing 1 1/2" (38.1 mm) apart
Application Width	40" (1.01 m)
Seed Gate	Automatic operation, adjustable variable opening
Ground Speed	Operating Speed: 3 MPH (4.8 km/h)
Transport Speed	Up to 6 MPH (9.6 km/h) (maximum)
Productivity	1.21 acres per hour at 3 MPH
Cutting Heads	2 heads, independently floating
Blade Assembly	2 WaveBlade sets, total 20 blades
Blade Assembly Operating Depth Range	0 to 1 3/8" (0 to 34.9 mm)
Engine	25 HP Briggs and Stratton Vanguard with electric start and 20 AMP charging system
Drive	Electric clutch with double groove V-belt
Hitch Type	Standard 5/8" pin, equipped with jackstand
Weight	1,070 lb (485 kg) <i>hopper empty</i>
Warranty	3 years
Optional	• Hydraulic Power Kit (HPU) (hose kit not needed when equipped with HPU) (#86196) • Hydraulic Hose Kit for use with Cushman Truck (#86505) • Hydraulic Hose Kit for use with Toro or John Deere Trucks (#86506)



Specifications subject to change without notice.

TriWave™ 60

Overseeder



TriWave technology creates optimum slits for improved seed-to-soil contact, while minimizing turf disruption.



Cover More Ground with Better Germination Rates

Golf course superintendents told us they wanted a seeder with better germination rates, but minimal turf disruption. Four patents later, the TriWave™ 60 delivered on that promise. Three floating heads follow the contour of the ground while the unique seed delivery system works with the WaveBlade technology to optimize seed-to-soil contact for maximum germination rates—all while minimizing turf disruption.

- 60-inch application width combines with close, 1½-inch spacing to give you the most productive, high-germination rate seeder available.
- Depth adjuster allows you to adjust to varying conditions or seed types in the field without tools.
- Patented floating heads and WaveBlade technology combine to ensure you won't damage sprinkler heads or other unmarked items.



Depth adjuster allows you to adjust to varying conditions or seed types.



Floating heads follow the ground contour.



Unmarked items will be undamaged.

Specifications

Model	TriWave 60 Overseeder (#85851)
Width	74" (1.88 m)
Height	51" (1.3 m)
Length	40" (1.02 m) <i>without PTO shaft</i>
Capacity	4.77 ft³ (8,251 in³)
Application Pattern	Seed spacing 1 ½" (38.1 mm) apart
Application Width	60" (1.52 m)
Seed Gate	Manually operated, variable opening
Ground Speed	Up to 5.5 MPH (8.85 km/h)
Productivity	Up to 3 acres per hour
Cutting Heads	3 heads, independently floating
Blade Assembly	3 WaveBlade sets, total 30 blades
Blade Assembly Operating Depth Range	0 to 1 ¾" (0 to 34.9 mm)
Tractor/Horsepower Requirements	35 HP minimum to 60 HP maximum (26.1 kW to 44.7 kW)
Drive	540 PTO (tractor)
Hitch Type	Category 1 or Category 2, 3-pt. hitch
Weight	1,150 lb (521.6 kg) <i>hopper empty</i>
Maximum Weight with Seed Hopper Full	Approximately 1,250 lb (567 kg)
Warranty	3 years
Options	TriWave 3-Point Extension Kit



Specifications subject to change without notice.